

US009510837B2

(12) United States Patent Seguin

(54) SURGICAL DEVICE FOR CONNECTING SOFT TISSUE

(71) Applicant: Evalve, Inc., Menlo Park, CA (US)

(72) Inventor: Jacques Seguin, Paris (FR)

(73) Assignee: Evalve, Inc., Menlo Park, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 182 days.

This patent is subject to a terminal dis-

claimer.

(21) Appl. No.: 14/259,772

(22) Filed: Apr. 23, 2014

(65) **Prior Publication Data**

US 2014/0236187 A1 Aug. 21, 2014

Related U.S. Application Data

(60) Division of application No. 13/156,760, filed on Jun. 9, 2011, now Pat. No. 8,740,918, which is a division of

(Continued)

(51) **Int. Cl.**A61B 17/00 (2006.01)

A61B 17/128 (2006.01)

(Continued)

(52) U.S. Cl.

CPC A61B 17/1285 (2013.01); A61B 17/00234 (2013.01); A61B 17/068 (2013.01); (Continued)

(58) Field of Classification Search

(10) Patent No.: US 9,510,837 B2

(45) **Date of Patent:**

*Dec. 6, 2016

A61B 2017/00601; A61B 2017/00606; A61B 2017/00668; A61B 2017/00654 See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

2,108,206 A 2/1938 Meeker 3,296,668 A 1/1967 Aiken (Continued)

FOREIGN PATENT DOCUMENTS

DE 3504292 7/1986 EP 0 179 562 AL 4/1986 (Continued)

OTHER PUBLICATIONS

Kavarna et al., "Transaortic repair of mitral regurgitation," Presented at the third annualNew Era Cardiac Care conference, San Diego, CA, Jan. 13-16, 2000 http://www.hsforum.com/vol3/issue1/2000-2389print.html.

(Continued)

Primary Examiner — Tuan V Nguyen (74) Attorney, Agent, or Firm — Sughrue Mion, PLLC; John Kwok

(57) **ABSTRACT**

Provided is a surgical instrument including an external tube (2) and two elongated members (4) positioned in the tube (2), each of which includes a distal end (10a) for capturing one of the two tissue zones (M1, M2) to be attached. The instrument (1) may further include a catching member (22, 25) for each tissue (M1, M2) to be attached; a rod (15, 16) linked to each catching member (22, 25) enabling tension to move axially, the rod (15, 16) being separable from said catching member (22, 25) when a tension is exerted on it beyond a certain threshold; and a member (17a) forming a stop for locking axially each catching member (22, 25) during the tensioning.

9 Claims, 4 Drawing Sheets

